

Bicolored light

Boat lengths to 20m

BSH/4615/6010261/06
D.06.261



Technical data

Diameter	64 mm
Height	59 mm
Input voltage range	9-28 V
Energy consumption	2,9 W
Source of light	selected LED
Wavelength	
green	505 nm +/-5 nm
red	625 nm +/-7 nm
Horizontal viewing angle	2 x 112,5°
Visibility	min 2 sm
Certified working time	20.000 h*
Operating temperature	-25°C bis 55°C
Storage temperature	-30°C bis 80°C
Weight	350 g
Enclosure	IP67 / IP68 (watertight)
Servicing	maintenance - free
Case	robust aluminum glas lens - no plastics



December 2006

*Within the life cycle the LED's efficiency gradually declines. Although LED's have a life cycle of about 100000h, the specified viewing range can be guaranteed only for 20000 operating hours. After that the lamp must be replaced

Note: LED radiation! Not with optical instruments regard and directly into the LED do not look

BlueWaterLights GmbH
Lange Wiese 7
D-07613 Crossen
Deutschland

Tel: ++ 49 (0) 36693 / 234780
Fax: ++ 49(0) 36693 / 23234
E-Mail: mail@bluewaterlights.de
Web: www.bluewaterlights.de

